

Product information

megol Motorenoel RACER SAE 10W-60 (vollsynthetisch)



Description

Modern motor oil, specially developed for use in high-load four-stroke engines. Optimally protects the engine against wear thanks to its synthetic base oils and innovative additive technology. The synthetic components provide it with a high performance level that is particularly effective in engines with extreme thermal requirements.

Note the manufacturer's instructions!

Specifications / Approvals

ACEA A3 • ACEA B4 • API SN • API CF

Characteristic data

SAE class (engine oils)	10W-60 SAE J300
Density at 15 °C	0,855 g/cm ³ DIN 51757
Viscosity at 40 °C	180,0 mm ² /s ASTM D7042
Viscosity at 100 °C	25,0 mm ² /s ASTM D7042
Viscosity at -30 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -25 °C (CCS)	≤ 7000 mPas ASTM D5293
Viscosity index	175 DIN ISO 2909
HTHS at 150°C	≥ 3,7 mPas ASTM D5481
Pour point	-36 °C DIN ISO 3016
Evaporation loss (Noack)	5,0 % CEC-L-40-A-93
Flash point	240 °C DIN ISO 2592
Total base number	10,5 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color number (ASTM)	L3,0 DIN ISO 2049

Available pack sizes

20 l Canister plastic	4353 DE-EN
60 l Black plate barrel	33067 DE-EN

Available pack sizes

1 l Canister plastic	6524 AR-DE-EN-ES-FR-IT-PT- RO-RU
----------------------	--