

# Product information

megol Zweitaktmotorenoel TC (teilsynthetisch)



## Description

High-quality, high-performance motor oil for the lubrication of two-stroke engines. Thanks to selected base oils on a synthetic and mineral base in combination with modern additive technology, ensures optimum lubrication and minimum smoke emissions (low smoke). Due to the specific viscosity setting, ideally suited both for separate and mixture lubrication in the respective specified mixture ratios of air and water-cooled two-stroke engines.

**Note the manufacturer's instructions!**

## Specifications / Approvals

API TC • ISO L-EGC • JASO FC • TISI (Thailand International Standards Institute)

## Characteristic data

Density at 15 °C	0,865 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	59,5 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	9,1 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity index	130 DIN ISO 2909
Pour point	-24 °C DIN ISO 3016
Flash point	110 °C DIN ISO 2592
Total base number	1,1 mg KOH/g DIN ISO 3771
Sulfate ash	0,06 g/100g DIN 51575
Color / appearance	red

## Available pack sizes

250 ml Dispensing bottle plastic	9026 DE-EN
1 l Canister plastic	9025 AR-DE-EN-ES-FR-IT-PT-RO-RU
20 l Canister plastic	4883 DE-EN
1.000 l Deposit container	9762 DE-EN