

Product information

Meguin Motor Flush



Description

Flushes out and cleans the engine from the inside. Highly effective cleaning additives dissolve sludge and lacquer formers, envelop solid dirt particles and liquid contaminants and are drained along with the motor oil during an oil change. Engines stripped of deposits and contaminants then can deliver their full performance when fresh oil is filled. For cleaning and flushing out the oil circuits of gasoline and diesel engines. The use is dependent on the degree of contamination of the oil circuit. Can be safely used in vehicles with toothed belt running in oil. Not suitable for use in motorbikes with wet clutches.



Properties

- tested for the use with catalytic converters
- highly economical
- gentle cleaning
- does not attack common sealing materials
- simple to use
- rapid cleaning

Characteristic data

Color / appearance	yellow, brown
Base	additive, carrier liquid
Flash point	63 °C DIN ISO 2592
Pour point	-45 °C DIN ISO 3016
Form	liquid
Viscosity at 40 °C	<7 mm ² /s
Odor	characteristic

Application

250 ml sufficient for up to 4 l of oil. Add to the motor oil at running temperature before changing the oil. After it has been added, let the engine idle for 10 – 15 minutes. Then change the oil and the filter. Compatible with commercially available motor oils.

Available pack sizes

250 ml Can sheet metal 6556
AR-DE-EN-FR-RU