

Product information

megol Motorenoel Efficiency SAE 5W-30



Description

High-performance motor oil based on Low-SAPS technology, which was specially developed for exhaust aftertreatment systems on the latest generation of diesel engines. Also suitable for gasoline engines. Meets the high performance requirements of modern engines and ensures maximum service life of the diesel particulate filter as well as low wear, good engine cleanliness and long oil change intervals.

Note the manufacturer's instructions!

Specifications / Approvals

ACEA C2, C3 • API SP • BMW Longlife-04 • MB-Approval 229.31 • MB-Approval 229.51 • MB-Approval 229.52

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Fiat 9.55535-S3 • Ford WSS-M2C 917-A • GM dexos2 • Opel OV 040 1547 - G30 / Opel OV 040 1547 - D30 • Opel GM-LL-A-025 • Opel GM-LL-B-025 • VW 505 00 • VW 505 01

Characteristic data

SAE class (engine oils)	5W-30 SAE J300
Density at 15 °C	0,850 g/cm ³ DIN 51757
Viscosity at 40 °C	71,0 mm ² /s ASTM D7042
Viscosity at 100 °C	12,2 mm ² /s ASTM D7042
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	<= 6600 mPas ASTM D5293
Viscosity index	170 DIN ISO 2909
HTHS at 150°C	≥ 3,5 mPas ASTM D5481
Pour point	-39 °C DIN ISO 3016
Evaporation loss (Noack)	9,0 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	7,5 mg KOH/g DIN ISO 3771

Characteristic data

Sulfate ash	≤ 0,8 g/100g DIN 51575
Color number (ASTM)	2,5 DIN ISO 2049

Available pack sizes

1 l Canister plastic	3196 AR-DE-EN-ES-FR-IT-PT-RO-RU
4 l Canister plastic	33062 AR-DE-EN-ES-FR-IT-PT-RO-RU
5 l Canister plastic	3194 AR-DE-EN-ES-FR-IT-PT-RO-RU
20 l Canister plastic	9480 DE-EN
60 l Black plate barrel	9481 DE-EN
200 l Black plate barrel	9482 DE-EN
1.000 l Deposit container	9483 DE-EN

