

# Product information

## megol Motorenoel Surface Protection SAE 5W-30



### Description

Low-friction motor oil for older and in some cases also newer generations of Ford vehicles. As a low-viscosity motor oil with high shear stability, reliably prevents the formation of deposits, reduces frictional losses in the engine and optimally protects against wear. This results in fuel savings and extended service life of the engine.

### Note the manufacturer's instructions!

### Specifications / Approvals

ACEA A5 • ACEA B5 • Ford WSS-M2C 913-D • Jaguar / Land Rover STJLR.03.5003 • VVC 53036

**Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:**

Ford WSS-M2C 913-A • Ford WSS-M2C 913-B • Ford WSS-M2C 913-C • Fiat 9.55535-G1

### Characteristic data

SAE class (engine oils)	5W-30 SAE J300
Density at 15 °C	0,855 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	53,0 mm <sup>2</sup> /s ASTM D7042
Viscosity at 100 °C	9,7 mm <sup>2</sup> /s ASTM D7042
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	≤ 6600 mPas ASTM D5293
Viscosity index	170 DIN ISO 2909
HTHS at 150°C	2,9 - 3,5 mPas ASTM D5481
Flash point	220 °C DIN ISO 2592
Pour point	-42 °C DIN ISO 3016
Evaporation loss (Noack)	12,0 % CEC-L-40-A-93
Total base number	12,0 mg KOH/g DIN ISO 3771
Sulfate ash	1,2 g/100g DIN 51575

### Characteristic data

Color number (ASTM)	L3,5
	DIN ISO 2049

### Available pack sizes

1 l Canister plastic	3193 AR-DE-EN-ES-FR-IT-PT-RO-RU
5 l Canister plastic	3192 AR-DE-EN-ES-FR-IT-PT-RO-RU
20 l Canister plastic	9476 DE-EN
60 l Black plate barrel	9477 DE-EN
200 l Black plate barrel	9478 DE-EN
1.000 l Deposit container	9479 DE-EN
1 l Bulk goods	9458 DE