

Product information

megol Motorenoel High Condition SAE 5W-40



Description

Premium low-friction motor oil for year-round use. Developed for modern injection engines with and without turbocharger. Guaranteed low viscosity and high shear stability thanks to synthetic base oils with a HC base and innovative additive technology. The perfectly tailored formulation prevents deposits, lowers friction losses and provides optimum protection for the engine against wear. This results in fuel savings and extended service life of the engine.

Area of application: Car.

SAPS level: High-SAPS.

Note the manufacturer's instructions!

Specifications / Approvals

ACEA A3 • ACEA B4 • API SP • BMW Longlife-01 • MB-Approval 229.5 • Porsche A40 • VW 502 00 • VW 505 00

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Fiat 9.55535-H2 • Fiat 9.55535-M2 • Fiat 9.55535-N2 • Opel GM-LL-B-025 • Peugeot Citroen (PSA) B71 2294 • Peugeot Citroen (PSA) B71 2296 • Renault RN 0710 • Renault RN 0700

Characteristic data

SAE class (engine oils)	5W-40 SAE J300
Density at 15 °C	0,855 g/cm ³ DIN 51757
Viscosity at 40 °C	88,0 mm ² /s ASTM D7042
Viscosity at 100 °C	14,8 mm ² /s ASTM D7042
Viscosity at -35 °C (MRV)	≤ 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	≤ 6600 mPas ASTM D5293
Viscosity index	180 DIN ISO 2909
HTHS at 150°C	≥ 3,5 mPas ASTM D5481
Pour point	-42 °C DIN ISO 3016
Evaporation loss (Noack)	10,0 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	10,5 mg KOH/g DIN ISO 3771

Characteristic data

Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color number (ASTM)	L 3,5 DIN ISO 2049

Available pack sizes

1 l Canister plastic	3199 AR-DE-EN-ES-FR-IT-PT-RO-RU
5 l Canister plastic	3198 AR-DE-EN-ES-FR-IT-PT-RO-RU
20 l Canister plastic	9484 DE-EN
60 l Black plate barrel	9485 DE-EN
200 l Black plate barrel	9486 DE-EN
1 l Bulk goods	9457 DE