

Product information

megol Motorenoel Syntech Premium SAE 10W-40



Description

Low-friction motor oil for year-round use in gasoline and diesel engines with and without turbocharging. Thanks to its optimum combination of base oils and additive technology, improves the engine performance and reduces friction and wear. Ideal for use in older vehicles (youngtimers).

Range of applications: Passenger cars.

SAPS level: High-SAPS.

Note the manufacturer's instructions!

Specifications / Approvals

ACEA A3 • ACEA B4 • API SP • API CF • MB-Approval 229.3 • VW 501 01 • VW 505 00

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

MB 229.1 • Peugeot Citroen (PSA) B71 2300

Characteristic data

SAE class (engine oils)	10W-40 SAE J300
Density at 15 °C	0,870 g/cm ³ DIN 51757
Viscosity at 40 °C	97,0 mm ² /s ASTM D7042
Viscosity at 100 °C	14,5 mm ² /s ASTM D7042
Viscosity at -30 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -25 °C (CCS)	≤ 7000 mPas ASTM D5293
Viscosity index	155 DIN ISO 2909
HTHS at 150°C	≥ 3,5 mPas ASTM D5481
Pour point	-36 °C DIN ISO 3016
Evaporation loss (Noack)	11,0 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	11,0 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575

Characteristic data

Color number (ASTM) 2,5
DIN ISO 2049

Available pack sizes

1 l Canister plastic	4339 AR-DE-EN-ES-FR-IT-PT-RO-RU
4 l Canister plastic	6475 AR-DE-EN-ES-FR-IT-PT-RO-RU
5 l Canister plastic	4338 AR-DE-EN-ES-FR-IT-PT-RO-RU
20 l Canister plastic	4797 DE-EN
60 l Black plate barrel	4798 DE-EN
200 l Black plate barrel	4799 DE-EN
1.000 l Container	6884 DE-EN
1.000 l Deposit container	9733 DE-EN
1 l Bulk goods	4680 DE