

# Product information

## megol Motorenoel Evolution LL IV SAE 0W-20



### Description

High-performance low-friction motor oil based on modern synthetic technology. As Longlife IV lubricant, optimizes fuel consumption and achieves additional fuel savings of approx. 1.5 % compared to the already fuel-optimized Longlife III. The reduced viscosity in combination with our additive package ensures excellent cold-start behavior, increases the efficiency of the engine and provides optimum wear protection and outstanding engine cleanliness. Ideally suited for extended oil change intervals (WIV, etc.) and heavy duty engine requirements. Specially developed for the requirements of various vehicle models from Audi, Seat, Škoda, Porsche and VW. Also suitable for vehicles with automatic start-stop system.

**Range of applications: Passenger cars.**

**Note the manufacturer's instructions!**

### Specifications / Approvals

ACEA C5 • Ford WSS-M2C 956-A1 • Porsche C20 • VW 508 00 • VW 509 00

### Characteristic data

Viscosity SAE class	0W-20 SAE J300
Density at 15 °C	0,845 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	44,0 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	8,4 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -35 °C (CCS)	≤ 6200 mPas ASTM D 5293
Viscosity index	180 DIN ISO 2909
HTHS at 150°C	≥ 2,6 mPas ASTM D 5481
Pour point	-45 °C DIN ISO 3016
Evaporation loss (Noack)	10,5 % CEC-L-40-A-93
Total base number	9,2 mg KOH/g DIN ISO 3771

### Characteristic data

Flash point	220 °C DIN ISO 2592
Sulfate ash	≤ 0,8 % DIN 51575
Color / appearance	greenish
Oil base	Advanced Full Synthetic

### Available pack sizes

1 l Canister plastic	33026 AR-DE-EN-ES-FR-IT-PT-RO-RU
5 l Canister plastic	33058 AR-DE-EN-ES-FR-IT-PT-RO-RU
20 l Canister plastic	33074 DE-EN
60 l Black plate barrel	33027 DE-EN
200 l Black plate barrel	33059 DE-EN