

Product information

megol Motorenoel Ecology SAE 5W-30



Description

Special motor oil with Low-SAPS technology and reduced HTHS. Specially tailored to suit the requirements of modern exhaust aftertreatment systems. Specially developed for passenger car diesel engines from Mazda and Mitsubishi. Ensures maximum service life of the diesel particulate filter as well as low wear, good engine cleanliness and long oil change intervals.

Note the manufacturer's instructions!

Specifications / Approvals

ACEA C1

Available pack sizes

5 l Canister plastic 3187

AR-DE-EN-ES-FR-IT-PT-RO-RU

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

JASO DL-1 • Ford WSS-M2C 934-B • Mitsubishi • Mazda

Characteristic data

SAE class (engine oils)	5W-30 SAE J300
Density at 15 °C	0,85 g/cm ³ DIN 51757
Viscosity at 40 °C	55 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	10 mm ² /s ASTM D 7042-04
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	≤ 6600 mPas ASTM D5293
Viscosity index	171 DIN ISO 2909
HTHS at 150°C	≥ 2,9 mPas ASTM D5481
Pour point	-42 °C DIN ISO 3016
Evaporation loss (Noack)	11,5 % CEC-L-40-A-93
Flash point	228 °C DIN ISO 2592
Total base number	6,5 mg KOH/g DIN ISO 3771
Sulfate ash	≤ 0,5 g/100g DIN 51575
Color number (ASTM)	2,5 DIN ISO 2049

Available pack sizes