

# Product information

megol Motorenoel Fuel Eco 1 SAE 0W-30



## Description

High-performance motor oil based on modern synthetic technology and a proven additive system. Low-viscosity motor oil with high shear stability and reduced HTHS. This results in fuel savings and extended service life of the engine.

## Note the manufacturer's instructions!

## Specifications / Approvals

ACEA A7/B7 • API SL • Volvo VCC 95200377

## Characteristic data

SAE class (engine oils)	0W-30 SAE J300
Density at 15 °C	0,845 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	51,7 mm <sup>2</sup> /s ASTM D7042
Viscosity at 100 °C	9,7 mm <sup>2</sup> /s ASTM D7042
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -35 °C (CCS)	≤ 6200 mPas ASTM D5293
Viscosity index	180 DIN ISO 2909
HTHS at 150°C	2,9 - 3,5 mPas ASTM D5481
Pour point	-45 °C DIN ISO 3016
Evaporation loss (Noack)	12,0 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	12,0 mg KOH/g DIN ISO 3771
Sulfate ash	1,2 g/100g DIN 51575
Color number (ASTM)	L3,5 DIN ISO 2049
Oil base	Advanced Full Synthetic

## Available pack sizes

20 l Canister plastic	33125 DE-EN
60 l Black plate barrel	33126 DE-EN
200 l Black plate barrel	9038 DE-EN
1 l Bulk goods	9039 DE

## Available pack sizes

1 l Canister plastic	33038 AR-DE-EN-ES-FR-IT-PT- RO-RU
5 l Canister plastic	33039 AR-DE-EN-ES-FR-IT-PT- RO-RU