

Product information

megol Motorenoel Compatible SAE 0W-30 FE Plus



Description

High-performance long-life motor oil based on HC synthetic base oils and modern Low-SAPS additive technology. Ensures optimum engine cleanliness, protects against wear and improves the effectiveness of the diesel particulate filter (DPF). The low viscosity ensures maximum fuel savings and efficiency, reduces emissions over the entire service life and helps protect the environment. Can be used in VW vehicles with and without extended maintenance intervals (WIV), in FSI engines and diesel vehicles, incl. those with a diesel particulate filter (DPF) and turbocharger (exception: R5 and V10 TDI engines before manufacture year 06/2006).

Area of application: Car

SAPS level: Low-SAPS

Note the manufacturer's instructions.

Specifications / Approvals

ACEA C3 • BMW Longlife-04 • MB-Approval 229.52 • VW 504 00 • VW 507 00

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Porsche C30

Characteristic data

Viscosity SAE class	0W-30 SAE J300
Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	60,0 mm ² /s ASTM D7042
Viscosity at 100 °C	11,9 mm ² /s ASTM D7042
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -35 °C (CCS)	≤ 6200 mPas ASTM D5293
HTHS at 150°C	≥ 3,5 mPas ASTM D5481
Viscosity index	200 DIN ISO 2909
Pour point	-48 °C DIN ISO 3016
Flash point	220 °C DIN ISO 2592
Evaporation loss (Noack)	10,0 % ASTM D5800 B

Characteristic data

Total base number	8,4 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575
Color number (ASTM)	L 2,5 DIN ISO 2049

Available pack sizes

1 l Canister plastic	33107 AR-DE-EN-ES-FR-IT-PT-RO-RU
5 l Canister plastic	33108 AR-DE-EN-ES-FR-IT-PT-RO-RU
20 l Canister plastic	33109 DE-EN
60 l Black plate barrel	33110 DE-EN
200 l Black plate barrel	33111 DE-EN
1.000 l Deposit container	33112 DE-EN