

Product information

megol Motorenoel New Engine FED SAE 0W-30



Description

High-performance motor oil based on synthetic base oils and modern Low-SAPS additive technology. Specially developed for the requirements of the latest Euro 6 diesel engines from Ford. Ensures the best possible engine cleanliness, prevents premature clogging of the diesel particulate filter, reduces emissions and protects the environment. Selected wear protection additives guarantee minimum friction with the highest fuel savings. Also suitable for vehicles with automatic start-stop system.

Range of applications: Passenger cars.

SAPS level: Low-SAPS.

Note the manufacturer's instructions!

Approvals

ACEA C2 • API SN • Ford WSS-M2C 950-A • Jaguar / Land Rover STJLR.03.5007

Characteristic data

Viscosity SAE class	0W-30 SAE J300
Density at 15 °C	0,85 g/cm ³ DIN 51757
Viscosity at 40 °C	49 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	9,5 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -35 °C (CCS)	< 6200 mPas ASTM D 5293
HTHS at 150°C	> 2,9 mPas ASTM D 5481
Viscosity index	185 DIN ISO 2909
Pour point	-42 °C DIN ISO 3016
Flash point	220 °C DIN ISO 2592
Evaporation loss (Noack)	12 % ASTM 5800B
Total base number	7,7 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575
Color number (ASTM)	L 2,5 DIN ISO 2049

Available pack sizes

1 l Canister plastic	33015 D-GB-F-HR-RUS-GR
5 l Canister plastic	33030 D-GB-F-HR-RUS-GR
20 l Canister plastic	33012 D-GB
60 l Black plate barrel	33013 D-GB
200 l Black plate barrel	33014 D-GB
1.000 l Deposit container	33016 D-GB