

Product information

megol Motorenoel Low Ash Energy SAE 0W-30



Description

High-performance motor oil based on synthetic base oils and modern Low-SAPS additive technology. Especially for PSA and Fiat Euro 6 engines with exhaust aftertreatment and turbocharging. Ensures optimum engine cleanliness, provides excellent wear protection, improves the effectiveness of the diesel particulate filter (DPF), prevents it from clogging prematurely, reduces emissions over its entire life, reduces fuel consumption and helps protect the environment. In addition to vehicles from PSA, Fiat and Alfa Romeo (TwinAir and MultiAir engines), also suitable for additional manufacturers that require a motor oil with this specification.

Range of applications: Passenger cars, light commercial vehicles (< 7.5 t).

SAPS level: Low-SAPS.

Note the manufacturer's instructions!

Specifications / Approvals

ACEA C2 • API SQ • Peugeot Citroen (PSA) B71 2312

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Fiat 9.55535-DS1 • Fiat 9.55535-GS1 • Peugeot Citroen (PSA) B71 2302

Characteristic data

SAE class (engine oils)	0W-30 SAE J300
Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	51,0 mm ² /s ASTM D7042
Viscosity at 100 °C	9,7 mm ² /s ASTM D7042
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -35 °C (CCS)	≤ 6200 mPas ASTM D5293
Viscosity index	175 DIN ISO 2909
HTHS at 150°C	≥ 2,9 mPas ASTM D5481
Pour point	-42 °C DIN ISO 3016
Evaporation loss (Noack)	10,9 % CEC-L-40-A-93

Characteristic data

Flash point	230 °C DIN ISO 2592
Total base number	10,5 mg KOH/g DIN ISO 3771
Sulfate ash	≤ 0,8 g/100g DIN 51575
Color number (ASTM)	L 4,5 DIN ISO 2049

Available pack sizes

1 l Canister plastic	33031 AR-DE-EN-ES-FR-IT-PT-RO-RU
5 l Canister plastic	33064 AR-DE-EN-ES-FR-IT-PT-RO-RU
20 l Canister plastic	33065 DE-EN
60 l Black plate barrel	33066 DE-EN
200 l Black plate barrel	33032 DE-EN
1.000 l Deposit container	33142 DE-EN